

A&G MANUFACTURING CO., INC.

YOUR SOURCE FOR QUALITY, SERVICE AND EFFICIENT BUYING.

PHONE 978-587-2859

WWW.AGMFG.NET

1-888-367-8227

POLYESTER MEASURE/PULLING TAPE



PART #	UPC#	DESCRIPTION	WEIGHT EACH
12125	12125	1/2" X 3,000' REEL 1250 LBS BREAKING STRENGTH	26 lbs.
58180	58180	5/8" X 3000' REEL 1800 LBS BREAKING STRENGTH	35 lbs.
34500	34500	3/4" X 500' REEL 2500 LBS BREAKING STRENGTH	24 lbs.
34150	34150	3/4" X 1500' REEL 2500 LBS BREAKING STRENGTH	24 lbs.
34250	34250	3/4" X 3000' REEL 2500 LBS BREAKING STRENGTH	46 lbs.
PT100600-2K	20060	1" X 2000' REEL 6000 LBS BREAKING STRENGTH	74 lbs.
31630	31630	CONDUIT MEASURING TAPE 3000' REEL, 160 LBS BREAKING STRENGTH	4 lbs.

PULL-LINE

FEATURES

- CONVENIENT BUCKET FEATURES PRE-PUNCHED TOP FOR EASY ACCESS
- CONTINUOUS-FIBER POLYLINE CAN BE BLOWN DIRECTLY INTO CONDUIT
- WILL NOT ROT OR MILDEW
- CAN BE LEFT IN CONDUIT FOR FUTURE USE
- COLOR-CODED FOR EASY LOCATION IN CONDUIT



PART #	UPC#	DESCRIPTION
26500	26500	Pull-Line - 6,500 feet long. 210 lb Minimum Tensile Strength
52200	52200	Pull-Line - 2,200 feet long. 500 lb Minimum Tensile Strength



#9 TWINE NYLON FISH LINE

PART #	UPC#	DESCRIPTION	SHIP	WEIGHT
92200	92200	2200' #9 Twine - 85lb Minimum Tensile Strength	10	10

978-587-2859

WWW.AGMFG.NET

1-888-367-8227