

A&G MANUFACTURING CO., INC.


YOUR SOURCE FOR QUALITY, SERVICE AND EFFICIENT BUYING.

PHONE 978-587-2859

WWW.AGMFG.NET

1-888-367-8227

STEEL CONDUIT LOCKNUTS



DESCRIPTION

A&G Mfg. steel locknuts are used to secure threaded conduits or connectors to electrical junction boxes or enclosures in wet/dry locations. The conduit locknuts allow standard junction boxes to be used with unthreaded conduit knockout openings in wet/dry locations. Serrated teeth on the locknut bite into the box and enclosure to prevent vibratory loosening of the connection. In damp locations, steel conduit locknuts are also of excellent corrosion protection with zinc electroplated.

PART #	UPC#	SIZE	THREADS per inch	UNIT CARTON	SHIP CASE	WEIGHT CASE	INCHES		
							A	B	THREAD PITCH DIAMETER
LN-S50	20050	1/2"	14	100	1000	10	1.15	1.15	.797 - 7.97
LN-S75	20075	3/4"	14	100	1000	20	1.45	1.45	.999 - 1.009
LN-S100	20100	1"	11-1/2	100	1000	30	1.75	1.75	1.25 - 1.26
LN-S125	20125	1-1/4"	11-1/2	100	1000	40	2.10	2.10	1.595 - 1.605
LN-S150	20150	1-1/2"	11-1/2	100	1000	60	2.40	2.40	1.837 - 1.847
LN-S200	20200	2"	11-1/2	50	500	40	2.95	2.95	2.307 - 2.317
LN-S250	20250	2-1/2"	8	--	50	6	3.55	3.55	2.777 - 2.788
LN-S300	20300	3"	8	--	50	9	3.55	3.55	3.403 - 3.414
LN-S350	20350	3-1/2"	8	--	50	12	4.20	4.20	3.892 - 3.904
LN-S400	20400	4"	8	--	50	14	4.75	4.75	4.399 - 4.411
LN-S500	20500	5"	8	--	10	5	6.67	6.67	5.488 - 5.50
LN-S600	20600	6"	8	--	10	8	7.93	7.93	6.545 - 6.557

- STEEL
- ELECTROPLATED ZINC
- FULL-CUT INTERNAL THREADS
- MEETS FEDERAL SPEC. A-A-50553

978-587-2859

WWW.AGMFG.NET

1-888-367-8227