

A&G MANUFACTURING CO., INC.

YOUR SOURCE FOR QUALITY, SERVICE AND EFFICIENT BUYING.

PHONE 978-587-2859

WWW.AGMFG.NET

1-888-367-8227

STRAIGHT LIQUIDTIGHT CONNECTORS WITH INSULATED THROAT - MALLEABLE IRON

FEATURES

- LIQUIDTIGHT, RAIN TIGHT, OIL TIGHT
- TAPERED THREADED MALE HUB NPT
- INSULATED THROAT PROTECTS CONDUCTORS FROM ABRASION DAMAGE
- COMPACT SLIM DIAMETER WITH SMALL TURNING RADIUS
- ZINC ELECTRO PLATED FOR EXCELLENT DURABILITY



APPLICATION

- TO SECURE, GROUND AND SEAL LIQUIDTIGHT CONDUIT TO A BOX OR ENCLOSURE
- UL LISTED LIQUIDTIGHT FLEXIBLE METAL CONDUIT FITTINGS ARE SUITABLE FOR USE IN THE FOLLOWING HAZARDOUS LOCATIONS UNDER: NEC 501-4(b), 502-4(a), (2)503-3(a) CLASS 1 DIV.2, CLASS II DIV. 1 AND 2, CLASS III DIV. 1 AND 2 AND ARE SUITABLE FOR GROUNDING IN SIZES 3/8" THROUGH 1-1/2" UNDER NEC 351-1



STANDARD MATERIAL


- MALLEABLE IRON
- STEEL LOCKNUT

STANDARD FINISH

- ZINC PLATED

APPLICABLE THIRD PARTY STANDARDS

- UL STANDARD: UL 514B
- FED. SPEC: W-F-406E, W-F-406D
- NEMA: FB 1-2014



PART #	UPC#	CONDUIT SIZE	UNIT CARTON	SHIP CASE	WEIGHT CASE	INCHES	
						A	B
MST-38	80055	3/8" - 1/2" KO	20	200	31	1.18	1.72
MST-50	80057	1/2"	20	200	33	1.36	1.73
MST-75	80058	3/4"	10	100	25	1.61	1.81
MST-100	80048	1"	5	50	18	1.89	1.85
MST-125	80049	1-1/4"	5	50	28	2.39	2.05
MST-150	80050	1-1/2"	2	20	15	2.62	2.38
MST-200	80051	2"	2	20	22	3.24	2.49
MST-250	80052	2-1/2"	---	1	2	3.89	3.21
MST-300	80053	3"	---	1	3	4.74	3.37
MST-350	80054	3-1/2"	---	1	4	5.31	3.40
MST-400	80056	4"	---	1	5	5.82	3.66

978-587-2859

WWW.AGMFG.NET

1-888-367-8227